

TECHNICAL SPECIFICATIONS

Performance

Payload	350
Certified Range	207 Km
Maximum Speed	45 km/h
Charging Time (0 to 80%)	4 hrs
On Board Charger	3 kW

Battery Power Pack

Battery Type	Lithium-ion
Capacity	13.2 kWh

Specification

Seating Capacity	D+3
Steering System	Handle Bar
Ground Clearance	190 mm
Wheelbase	1950 mm
Turning Radius	2.65 m
Gradeability	21.26%
Overall Length	2836mm
Overall Width	1390mm
Overall Height	1890mm
Tyres	135/70 R12

Suspension System

Front	Fork Type With Double Helical Compression Coil Spring, Telescopic Hydraulic Shock Absorber
Rear	Trailing Arm, Helical Compression With Coil Spring Telescopic Shock Absorber

Motor

Type	AC Synchronous Motor
Power Peak	9.9 kW
Torque Peak	44 Nm

Brake System

Front & Rear	Hydraulic
--------------	-----------

Technology

Battery Thermal Management System	Active Intelligent Cooling
Regenerative Braking	Efficient Energy Recovery
Vehicle Telemetry System	Atul Intelligence (AI) Platform
IP 67 Rated Components	Motor, Charger, Battery & All connectors



**ATUL
RIK TWIN**

The Future of Electric Passenger Vehicles

—Engineered in Europe, Built in India.

ATUL AUTO LIMITED

Marketing Head Office: 406, Baleshwar Square, Opp. Iscon Mall, S.G. Highway,

Ahmedabad - 380015, Gujarat - India.

Customer Care: 89 888 70 999 Email: marketing@atulauto.co.in

www.atulauto.co.in [f](#) atulautold [@](#) atul_auto_ltd

Authorised Dealer

LAMBA SAFAR, ZERO FIKAR



Double Battery, Double Range

ATUL RIK TWIN



Industry's Best Mileage
*APPROVED ARAI CERTIFICATION



Fast Charging
0 to 80% in 6 hours



**Wider Driver &
Passenger Space**



YEAR WARRANTY